



# Protecting Indoor Air and Surfaces™



## Features ActivePure Technology proven to reduce viruses, bacteria, and other pathogens (full list of tested pathogens available below in "The Proof")

### THE TECHNOLOGY

The Aerus® AP500 is our smallest-profile product Powered by ActivePure® Technology, mounting directly into a standard wall outlet. Patented ActivePure Technology is an advanced surface and air purification technology. It has been proven to reduce over 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in "The Proof" section below).

ActivePure Technology does not replace the need to follow public health guidelines and should be used as complementary technology.

### THE PROOF

In extensive unaffiliated lab testing, ActivePure® Technology has been proven to significantly reduce the following contaminants and pathogens<sup>1</sup>:

- SARS-CoV-2
- Staphylococcus Aureus
- Aspergillus niger endospores
- H1N1 Influenza
- H5N8 Influenza
- MRSA
- Bacillus globigii
- MS2 Bacteriophage
- Staphylococcus epidermidis
- PhiX-174
- Erwinia Herbicola
- Listeria monocytogenes
- Murine Norovirus
- E. coli
- Candida auris
- Botrytis cinerea
- Sclerotinia sclerotiorum
- Legionella pneumophila
- Aspergillus versicolor
- Clostridium difficile
- Salmonella enterica


### THE BENEFITS

The AP500 utilizes our proprietary ActivePure Technology to effectively treat indoor air and exposed surfaces, helping to reduce surface and airborne contaminants, allergens, and odors. A powerful, inconspicuous air purification system intended for use in small spaces.

- Disinfects surfaces and air, removes VOC gases, smoke and odor
- Compact, natural air treatment system for up to 250 sq. ft.
- Plugs into standard 120 volt electrical outlet
- Anti-theft mounting arrangement, no wiring required



<sup>1</sup> View test results at [Aerusonline.com/Scientific-Proof](http://Aerusonline.com/Scientific-Proof)



Inducted into the 2017 Space Technology Hall of Fame by the Space Foundation

Assembled in USA



## SPECIFICATIONS

**Product Information** 00693 Model: A1028A  
**This unit does not meet California requirements and can not be shipped in California.**

**Technology Included** ActivePure® Technology

**Electrical** Supply Voltage: 120V~, 60 Hz, .18 Amp,  
Power Consumption: 13 Watts

**Mechanical** One control switch, on/off

**Weight & Dimensions** 2.9 lbs (1.3 kg)  
12"H x 6"W x 4"D  
(30 cm H x 15.24 cm W x 10 cm D)

**Coverage<sup>1</sup>** Up to 250 sq. ft. (23 m<sup>2</sup>) depending on occupant density and other factors<sup>1</sup>.  
High density commercial not to exceed 100 sq. ft. (9 m<sup>2</sup>).

**Warranty** Limited 3 year warranty



Contact Name: \_\_\_\_\_



Email: \_\_\_\_\_



Phone Number: \_\_\_\_\_

1. Assumes 8 foot ceilings. Solutions should be customized based upon a variety of factors including HVAC system capabilities and settings, air flows taking into account walls, air pressure, and doors, ambient air temperatures and humidities, variable density, known VOC concentrations, and other layers of protection.