

Proven to reduce 99.98% of SARS-CoV-2 virus (the virus that causes COVID-19) on surfaces within 7 hours.

THE TECHNOLOGY

The Aerus® Mid-Range Blaster is a device intended for the reduction of viruses, bacteria, and other contaminants in large indoor spaces up to 5,000 sq. ft. (464 m²). It has been proven to reduce over 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in "The Proof" section below). The Blaster was originally designed for spaces up to 20,000 sq. ft. (1,858 m²), but in light of the Delta variant, which has been reported to be 4 or more times more contagious than previous SARS-CoV-2 strains, we have adjusted our sizing guidelines and now recommend using the Blaster for a maximum of 5,000 sq. ft. (464 m²).

ActivePure Technology does not replace the need to follow public health guidelines and should be used as a complementary technology.

THE PROOF

In extensive unaffiliated lab testing, ActivePure® Technology has been proven to significantly reduce the following contaminants and pathogens¹:

- · SARS-CoV-2
- Staphylococcus aureus
- Aspergillus niger endospores
- H1N1 Influenza
- H5N8 Influenza
- MRSA
- Bacillus globigii
- · MS2 Bacteriophage
- Staphylococcus epidermidis
- PhiX-174

- · Erwinia herbicola
- Listeria monocytogenes
- · Murine Norovirus
- · E. coli
- · Candida auris
- · Botrytis cinerea
- · Sclerotinia sclerotiorum
- Legionella pneumophila
- Aspergillus versicolor
- Clostridium difficile
- · Salmonella enterica

THE BENEFITS

The Aerus Mid-Range Blaster provides 24/7 surface decontamination and air purification without the use of ozone. It is a proactive and effective solution for your home or business.

- ActivePure Technology delivers 24/7 surface decontamination and air purification technology
- Patented ActivePure® Technology has been proven to reduce over 99.9% of many common airborne and surface contaminants including viruses, bacteria, mold, fungi, VOC gases, smoke, allergens, and odors¹
- Portable unit is easy to move for versatility







Hall of Fame by



Inducted into the Assembled in USA 2017 Space Technology







Product Information	O0667; Model F213A This unit does not meet California requirements and cannot be shipped to California. Validated to UL 2998
Technology Included	ActivePure® Technology – (4) 9" Cells
Electrical	Input Voltage: 120V Power Consumption: 172W
Mechanical	Fuse: 2.25A; 2.0A slowblow Airflow Rate: 300 CFM
Safety	Conforms to UL 507
Weight & Dimensions	24 lbs (10.9 kg) (unpackaged) 22" H x 13" W x 13" D (48.26 cm x 33.02 cm x 33.02 cm)
Sound Level	57.4 dB(A)
Coverage ¹	Up to 5,000 sq. ft. (464 m²) depending on occupant density and other factors.
Warranty	Limited 3 year warranty
PONTE LE CANDOLOGY	Contact Name: Email: Phone Number:

^{1.} Assumes 8 foot ceilings. Solutions should be customized based upon a variety of factors including HVAC system capabilities and settings, air flows taking into account walls, air pressure, and doors, ambient air temperatures and humidities, variable density, known VOC concentrations, other layers of protection. Testing actual application results before and after utilization of the technology, in as near as possible identical conditions, is a recommended measure to optimize effective deployment.